## CLAIMS

1. A hose for a fuel feed device of a motor vehicle, with an elastic and electrically conductive wall, characterized in that the wall (3, 7, 11, 16) consists of an electrically nonconductive plastic and has at least one electrical conductor (4, 6, 12-14) connected to one end of the hose.

2. The hose as claimed in claim 1, characterized in that the electrical conductor (4, 6, 12-14) is arranged parallel to the axis of the hose or peripherally on the surface of the wall (3, 7, 11, 16).

3. The hose as claimed in claim 1 or 2, characterized in that the electrical conductor (4, 6, 12, 13) is designed as a track connected to the wall (3, 7, 11) in a materially integral or positive manner.

4. The hose as defined in claim 1, characterized in that the wall (16) has a conductive sheathing (15).

5. The hose as defined in claim 4, characterized in that the sheathing (15) is designed as a fabric hose.

6. The hose as defined in 1, characterized in that the electrical conductor (12) connects the outside and the inside of the wall (11) to one another in an electrically conductive manner.

7. The hose as defined in claim 1, characterized in that the electrical conductor (4, 6, 12-14) is manufactured from conductive plastic.

8. The hose as defined in claim 1, characterized in that the conductor (4, 6, 12, 13) is designed as part of the wall (3, 7, 11).

9. The hose as defined in claim 1, characterized in that the hose is designed as a corrugated hose.